



PRECISION BEARING CORP.

SRS9XGN[SS,SSHH,UU]+[52-900/1]LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. SRS9XGN[SS,SSHH,UU]+[52-900/1]LM

SRS9XGN[SS,SSHH,UU]+[52-900/1]LM Bearing
2D drawings and 3D CAD models

Days to Ship	22 Days
Block Type	[Long] N: Long
The number of LM blocks combined with a axis	1
Nominal Part Number	9
Rail Type	Standard
Rail Width W1	9 mm
Mounting Height M	10 mm
Rail Length L	52 ~ 900 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	2940
Basic Load Rating Static Rating Co(N)	4590
Allowable Static Moment MA(N m)	21.1
Allowable Static Moment MB(N m)	24.4
Allowable Static Moment MC(N m)	21.1
Symbols for Dust Resistance	UU: End Seals
Advanced Seal Options (Longer Leadtime)	SSHH: SS + Laminated Contact Scraper LaCS
Block external dimension	20 mm



PRECISION BEARING CORP.

W	
Block external dimension L	40.8 mm
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	29.8 mm